

Accessories

Voltage Test Leads + Alligator Clips		(2m) × 5 pcs	Soft Carry Bag		1 pcs
			CD (Software, Manuals)		1 pcs
Power Cord Power Adapter		1 pcs	Sticker of input port (Only SA2200)		1 pcs

Clamp Mode	ST08	CTC0080	CTC0130	CTC1535	ETCR035AD
Apperance					
Measurement Range	0~5A	0~50A	1~100A	1~1000A	0.0~1000A (AC/DC)
Output Voltage Ratio	10mV/A	10mV/A	1mV/A	1mV/A	1mV/A
Accuracy	0.2%	0.2%	0.2%	1%	±3%
Frequency Characteristic	45Hz~55Hz	50Hz~400Hz	50Hz~400Hz	40Hz~100kHz	AC: 45Hz~400Hz
Clamp Radius (mm)	8	8	13	52	30×35
Dimension (mm)	158×43×24	171×46×27	174×52×27	111×216×45	122×70×33
Cable Length (cm)	200	200	200	200	150
Power	○	○	○	○	9V Dry cell 6LR61

Flexible Probes Mode	SY-1500A	PY-3000A	PY-5000A	SY-6000A
Apperance				
Measurement Range	10~1500A	15~3000A	20~5000A	20~6000A
Output Voltage Ratio@50Hz	100mV/1000A	65mV/1000A	50mV/1000A	65mV/1000A
Accuracy	±0.5% + Position Error	±1% + Position Error		±1% + Position Error
Maximum Allowable Input	100KA	100KA		100KA
Phase Error	<±1°	<±1°		<±1°
Noise	<2mVrms (10Hz~10KHz)	<2mVrms (10Hz~10KHz)		<2mVrms (10Hz~10KHz)
Frequency Characteristic	10Hz~10KHz (-3dB)	10Hz~10KHz (-3dB)		10Hz~10KHz (-3dB)
Weight	110g	130g		150g
Length	200cm	200cm		200cm
CT Perimeter	35cm	50cm		80cm
Measurement Position Error	±1%	±2%		±2%

• Our company reserves the right to change the specification of the catalogue without notice